Inkjet Specifications

- MFD, Expiry Date, batch, graphics, Logo, counter, date, time, shift etc.
- 1~4 lines printing
- Multi Chinese fonts available, and can be customized the font
- Printing speed: 200m/min (5x5, single line)
- Direct input simplified Chinese, traditional Chinese, English, Arabic, Persian, Russian, German, etc.

Interface & Communication

- 7" TFT color screen, with int'l standard QWERT keypad
- USB disk, to save/restore text & config, to load logos from PC to printers, to upgrade software
- Ethernet port (10/100MB)
- ♦ RS232/485 port

Electronic & Software Features

- 32 digits embedded LINUX operation system
- User friendly interface, WYSIWYG display
- Storage memory 40MB
- "RUN/STOP" hot key to start/stop printer automatically
- "INFO" hot key to list the history of errors to ease maintenance
- "PRINT MENU" hot key to activate printing instantly
- USB/Ethernet software upgrading
- Pop-up window to remind changing filters in every 2,000 hours
- Real time and date with calendar
- Printing mode: Standard, Multi-line High Speed, Graphic
- Text format: Horizontal-reverse, Vertical-reverse, Negative, Double Space, Bold, Character Width
- Defined grid value to move the editing cursors at a certain dot
- 3 counters & 4 shifts, automatically
- Build-in graphic/logo editing software as standard, full screen
- OPS(Encoder Direction Recognition & Printing Compensation Function)
- DMS(Distance Measuring System)
- Passwords give accesses to different users
- Multi operation language available

Hydraulic System

- ♠ Compact design, easy to use and service
- Detector in solvent bottle to give alarm when no
- Head embedded magnifying glass with LED, easy to check shape of drops
- Positive air inlet to print head for dusty environment

Full range of inks available

Certification/Standard approved

- CE (EMC, MD&LVD)


Physical Features


- - Umbilical hose standard: Length 2,500mm, Diameter 20mm


- Electrical plug, multi type available

- PC logo software
- Alarm system, 3 colors
- Speed adjustable conveyor

Dimension of Main Cabinet







Shanghai Rottweil Handyware Printing Technology Co., Ltd

T15-1-4, No.999 Ningqiao Rd., Jinqiao EPZ

Pudong New District, Shanghai 201206 Tel: +86-21-5834-8225

Fax: +86-21-5834-8193

Email: info@rottweilglobal.com

Website: www.rottweilglobal.com www.rottweil.com.cn

- Printer house/Cabinet: IP54 stainless steel
- Printer dimension: H558.5 x W398x D305mm
- Print head dimension: H185.5x W43x D49mm
- Power supply: Single phase, 110~220V, 50/60HZ
- Work temperature: 5~45C(35~100F)
- Work humidity: max.90% R.H., non-condensing

Optional Accessories

- Photo sensor
- Sliding table
- Shaft encoder
- ♦ L shape head



Endurable

Easy



Economical





E- jet 455CB

Small character Inkjet Printer ■ ■ ■

PIPE SPECIALIZED PRINTER

Professional technology

Excellent quality

Easy to Use

SIMPLE & FASY DESIGN FOR OPERATION & SERVIC

- 7" TrueColor Screen with WYSIWYG display Quick start-up & print, with "PRINT MENU" hot key
- "INFO" hot key to check historical log
 Build-in logo editor to create/edit logos easily at any time you want
- Head-embedded magnifying glass with LED to observe ink drops
- Positive air to print head is available to keep head clean & dry under tough working condition













Endurable to Trust

ONE OF THE MOST RELIABLE INK SYSTEMS

- Imported key high quality components
- Isolated ink system and electrical system
- IP54 stainless steel cabinet provides full protection against harsh production environment
- Hardened umbilical for tough working condition

Economical to Have

SAVE COST IN DAILY USE, BUDGET-WISE CHOICE

- Specialized key parts, reduce the consumption of solvent
- Special design of big Volume Solvent Container (2.7L) reduce the fill time during printing
- Solvent Level Sensor device, remind to refill the solvent





Big solvent reservior (2.7L) with condenser


Six features of E jet 455CB

- Big Volume Solvent Container (2.7L), reduce the fill time during printing
- Minimum consumption of solvent with condenser
 Running in 25 °C Condition, consume only 4.5ml per hour
- Refill type of ink and solvent, no hidden cost, no waste
- No limit for the length of text
- No chip for consumable, no waste of your consumable
- Core Spare Parts, without default running time



Operation panel, LINUX system









Printing Samples

E-jet 455CB Standard Printing Mode					
	1 line	2 lines			
5 dots	ABCDEF61234567	<u>∆.†</u> ☆2016/08/17 □¶02014/08/18	7 8		
	1 line	2 lines	3 lines	4 lines	
7 dots	ABCDEF61234567	合格 2016/08/ 合格 2014/08/	17 LOT:1408001a 18 MFG:14/08/18 18 EXP:16/08/17	BAT:0875E-24 LOT:1408001a MFG:14/08/18 EXP:16/08/17	
	1 line	2 lines	S		
11 dots	美创力小字符 ABCDefah5678 有效日期:2016/08/17 生产日期:2014/08/18				
	1 line				
16 dots	美创力小字符 ABCDef sh5678				
All types of font format, Arabic, Chinese					

Garlock



